

FITTINGS

Connections, fittings and accessories for pneumatics made of high quality brass.


PAY ATTENTION TO THE FF SYMBOL that indicates the steel swiveling connections which prevent pipe distortion during their operation, max pressure 10 bar.

Designed with the exclusive assembly system by means of stainless steel snap rings and Buna-N O-RINGS positioned on the exterior of the air passage outlet which allow an air flow with no need for narrowing and with an excellent seal.

COUPLINGS

Male sliding cock

Ref.	Thread
12341	1/4"



Package: 25 pcs

Male drain cock

Ref.	Thread
12370	1/8"
12371	1/4"
12372	3/8"
12373	1/2"



Package: 25 pcs

CONNECTIONS

Bayonet female

Ref.	Thread
13000	1/8"
13001	1/4"
13002	3/8"



Package: 25 pcs

Bayonet with rest

Ref.	Ø int. hose
13060	6
13061	7
13062	8



Package: 25 pcs

Bayonet male


Ref.	Thread
13010	1/8"
13011	1/4"
13012	3/8"



Package: 25 pcs

Swiveling bayonet connection for rilsan or nylon hose

Ref.	Ø int. - Ø ext.
13090	4x6
13091	6x8
13092	8x10
13093	10x12



FF

Package: 25 pcs

Bayonet for rubber hose

Ref.	Ø int. - Ø ext.
13023	6x14
13033	8x14
13027	8x17
13028	10x17
13029	10x19



Package: 25 pcs

Female for rubber hose

Ref.	Thread	Ø int. - Ø ext.
13106	1/4"	6x14
13115	1/4"	8x14
13110	1/4"	8x17
13114	3/8"	6x14
13119	3/8"	8x14
13116	3/8"	8x17



Package: 25 pcs

Male for rubber hose


Ref.	Thread	Ø int.-Ø ext.
13133	1/8"	8x17
13136	1/4"	6x14
13143	1/4"	8x14
13140	1/4"	8x17
13144	3/8"	6x14
13149	3/8"	8x14
13146	3/8"	8x17



Package: 25 pcs

Fixed bayonet for nylon or rilsan hose


Ref.	Ø int.-Ø ext.
13180	4x6
13181	6x8
13182	8x10
13183	10x12



Package: 25 pcs

Fixed male with rest for every type of hose


Ref.	Thread	Ø int. hose
13231	1/8"	6
13232	1/8"	7
13250	1/8"	8
13251	1/8"	9
13233	1/4"	5
13234	1/4"	6
13235	1/4"	7
13236	1/4"	8
13237	1/4"	9
13253	1/4"	10
13254	1/4"	15
13238	1/4"	11
13239	3/8"	8
13240	3/8"	9
13256	3/8"	10
13257	3/8"	12
13258	3/8"	13
13247	3/8"	14
13248	3/8"	16
13242	1/2"	11
13243	1/2"	12
13244	1/2"	15
13245	1/2"	17
13246	1/2"	19



Package: 25 pcs

Swiveling female connection for rilsan or nylon hose


Ref.	Thread	Ø int.-Ø ext.
13220	1/4"	4x6
13221	1/4"	6x8
13222	1/4"	8x10
13223	3/8"	6x8
13224	3/8"	8x10
13225	3/8"	10x12



FF
Package: 25 pcs

Swiveling female for polyurethane hose


Ref.	Thread	Ø int.-Ø ext.
13190	1/4"	5x8
13191	1/4"	6x10
13192	1/4"	6.5x10
13193	1/4"	8x12
13194	1/4"	10x15



FF
Package: 25 pcs

Fixed female with rest for every type of hose


Ref.	Thread	Ø int. hose
13260	1/8"	5
13261	1/4"	5
13262	1/4"	6
13263	1/4"	7
13264	1/4"	8
13265	1/4"	9-10
13266	3/8"	7
13267	3/8"	8
13268	3/8"	9-10
13269	3/8"	11
13271	1/2"	12



Package: 25 pcs


Double rest

Ref.	Ø int.-Ø ext.
13300	5
13301	6
13303	8
13304	9-10
13305	11




Package: 25 pcs

Swiveling male for polyurethane hose

Ref.	Thread	Ø int.-Ø ext.	FF
13311	1/4"	5x8	 Package: 25 pcs
13312	1/4"	6.5x10	
13326	1/4"	6x10	
13327	1/4"	8x12	
13315	3/8"	8x12	
13316	1/2"	9x12	
13317	1/2"	10x16	


Fixed male for nylon or rilsan hose

Ref.	Thread	Ø int.-Ø ext.
13200	1/4"	4x6
13201	1/4"	6x8
13202	1/4"	8x10
13204	3/8"	8x10
13205	3/8"	10x12




Package: 25 pcs


Swiveling male for nylon or rubber hose

Ref.	Thread	Ø int.-Ø ext.	FF
13210	1/4"	4x6	 Package: 25 pcs
13211	1/4"	6x8	
13212	1/4"	8x10	
13213	3/8"	6x8	
13214	3/8"	8x10	
13215	3/8"	10x12	
13216	1/2"	12x15	
13208	3/8"	9x12	
13209	3/8"	11x14	
13217	1/2"	15x20	

Swiveling male with rest for every type of hose

Ref.	Thread	Ø int. hose	FF
13330	1/4"	6	 Package: 25 pcs
13331	1/4"	7	
13332	1/4"	8	
13333	1/4"	9	
13334	1/4"	10	
13335	1/4"	11	
13336	3/8"	6	
13337	3/8"	8	
13338	3/8"	9	
13339	3/8"	10	
13340	3/8"	11	
13341	3/8"	12	
13342	3/8"	13	

Swiveling female with rest for every type of hose

Ref.	Thread	Ø int. hose	FF
13360	1/4"	6	 Package: 25 pcs
13361	1/4"	7	
13362	1/4"	8	
13363	1/4"	9	
13364	1/4"	10	
13365	3/8"	6	
13366	3/8"	7	
13367	3/8"	8	
13368	3/8"	9	
13369	3/8"	10	

FITTINGS

Milled nut

Ref.	Thread
14000	1/4"
14001	14x1.25
14002	3/8"



Package: 25 pcs

Female with milled nut

Ref.	Thread
14010	1/4"
14011	3/8"



Package: 25 pcs

Male with milled nut

Ref.	Thread
14021	1/4"
14022	3/8"



Package: 25 pcs

Double with milled nut

Ref.	Thread
14030	1/4"



Package: 25 pcs

T with milled nuts

Ref.	Thread
14040	1/4"



Package: 25 pcs

Cylindrical plug


Ref.	Thread
14250	1/8"
14251	1/4"
14252	3/8"
14253	1/2"
14254	3/4"



Package: 25 pcs

Cylindrical nipple

Ref.	Thread
14100	1/8" - 1/8"
14101	1/4" - 1/4"
14102	3/8" - 3/8"
14103	1/2" - 1/2"
14104	1/8" - 1/4"
14105	1/8" - 3/8"
14107	1/4" - 3/8"
14108	1/4" - 1/2"
14109	3/8" - 1/2"
14110	1/2" - 3/4"
14111	3/4" - 3/4"



Package: 25 pcs

Conical nipple

Ref.	Thread
14130	1/8" - 1/8"
14131	1/4" - 1/4"
14132	3/8" - 3/8"
14133	1/2" - 1/2"
14134	1/8" - 1/4"
14135	1/8" - 3/8"
14136	1/4" - 1/2"
14137	1/4" - 3/8"
14138	3/8" - 1/2"
14139	1/2" - 3/4"



Package: 25 pcs

Cylindrical reduction

Ref.	Thread
14140	M 1/4" - F 1/8"
14141	M 3/8" - F 1/8"
14142	M 3/8" - F 1/4"
14143	M 1/2" - F 3/8"
14144	M 1/2" - F 1/4"
14145	M 3/4" - F 1/2"
14146	M 3/4" - F 3/8"
14147	M 1/2" - F 1/8"



Package: 25 pcs

Conical reduction

Ref.	Thread
14150	M 1/4" - F 1/8"
14151	M 3/8" - F 1/8"
14152	M 3/8" - F 1/4"
14153	M 1/2" - F 3/8"
14154	M 1/2" - F 1/4"
14155	M 3/4" - F 1/2"
14156	M 3/4" - F 3/8"



Package: 25 pcs

Extension

Ref.	Thread
14170	M 1/8" - F 1/8"
14171	M 1/8" - F 1/4"
14172	M 1/8" - F 3/8"
14174	M 1/4" - F 1/8"
14175	M 1/4" - F 1/4"
14176	M 1/4" - F 3/8"
14179	M 3/8" - F 1/4"
14180	M 3/8" - F 3/8"
14181	M 3/8" - F 1/2"
14184	M 1/2" - F 3/8"
14185	M 1/2" - F 1/2"



Package: 25 pcs

Double female

Ref.	Thread
14200	1/8" - 1/8"
14201	1/4" - 1/4"
14202	3/8" - 3/8"
14203	1/2" - 1/2"
14204	1/8" - 1/4"
14205	1/8" - 3/8"
14206	1/2" - 1/8"
14207	1/4" - 3/8"
14208	1/4" - 1/2"
14209	3/8" - 1/2"



Package: 25 pcs

L male/female

Ref.	Thread
14300	1/8"
14301	1/4"
14302	3/8"
14303	1/2"



Package: 25 pcs

T female/male/female

Ref.	Thread
14340	1/8"
14341	1/4"
14342	3/8"
14343	1/2"



Package: 25 pcs

L female/female

Ref.	Thread
14310	1/8"
14311	1/4"
14312	3/8"
14313	1/2"



Package: 25 pcs

T female/female/female

Ref.	Thread
14350	1/8"
14351	1/4"
14352	3/8"
14353	1/2"



Package: 25 pcs

L male/male

Ref.	Thread
14315	1/8"
14316	1/4"
14317	3/8"
14318	1/2"



Package: 25 pcs

T female/female/male

Ref.	Thread
14355	1/8"
14356	1/4"
14357	3/8"
14358	1/2"



Package: 25 pcs

Y female/male/female

Ref.	Thread
14320	1/8"
14321	1/4"
14322	3/8"
14323	1/2"



Package: 25 pcs

T male/male/male

Ref.	Thread
14360	1/8"
14361	1/4"
14362	3/8"
14363	1/2"



Package: 25 pcs

Y female/female/female

Ref.	Thread
14330	1/8"
14331	1/4"
14332	3/8"
14333	1/2"



Package: 25 pcs

Cross F.F.F.M.

Ref.	Thread
14370	1/8"
14371	1/4"
14372	3/8"
14373	1/2"



Package: 25 pcs

Cross M.M.M.M

Ref.	Thread
14375	1/8"
14376	1/4"
14377	3/8"
14378	1/2"



Package: 25 pcs

Cross F.F.F.F.

Ref.	Thread
14380	1/8"
14381	1/4"
14382	3/8"
14383	1/2"



Package: 25 pcs

Male quick plug "D" with milled nut

Ref.	Thread
11045	1/4"



Package: 25 pcs

Bayonet seals

Ref.
60920




Package: 100 pcs

ACCESSORIES FOR PNEUMATIC

NEEDLE AIR LINE TAPS

Male with milled nut

Ref.	Thread
12010	1/4"
12011	3/8"
12012	1/2"



Package: 25 pcs

MINI BALL VALVES

Male with milled nut

Ref.	Thread
12110	1/4"
12111	3/8"



Package: 25 pcs

Male/Male

Ref.	Thread
12131	1/4"
12132	3/8"



Package: 25 pcs

Female/Female

Ref.	Thread
12150	1/8"
12151	1/4"
12152	3/8"
12153	1/2"



Package: 25 pcs

Male/ Female

Ref.	Thread
12170	1/8"
12171	1/4"
12172	3/8"
12173	1/2"




Package: 25 pcs

QUICK FITTINGS

Cylindrical male


Ref.	Thread	Ø int. - Ø ext.
15000	1/8"	4x6
15001	1/4"	4x6
15002	1/8"	6x8
15003	1/4"	6x8
15006	1/4"	8x10
15007	3/8"	8x10
15009	3/8"	10x12



Package: 25 pcs

Straight


Ref.	Ø int. - Ø ext.
15070	4x6
15071	6x8
15072	8x10
15073	10x12



Package: 25 pcs

L male


Ref.	Thread	Ø int. - Ø ext.
15090	1/8"	4x6
15093	1/4"	6x8
15096	1/4"	8x10
15098	1/2"	8x10
15099	3/8"	10x12



Package: 25 pcs

L female


Ref.	Thread	Ø int. - Ø ext.
15121	1/4"	6x8



Package: 25 pcs

Elbow


Ref.	Ø hose
15140	4x6
15141	6x8
15142	8x10
15143	10x12



Package: 25 pcs

T central male


Ref.	Thread	Ø hose
15160	1/8"	4x6
15162	1/8"	6x8
15163	1/4"	6x8
15164	3/8"	6x8
15165	1/8"	8x10
15166	1/4"	8x10
15169	3/8"	10x12



Package: 25 pcs

T EE


Ref.	Ø int. - Ø ext.
15180	4x6
15181	6x8
15182	8x10
15183	10x12



Package: 25 pcs

Blocking nut

Ref.	Ø hose
15400	4x6
15401	6x8
15402	8x10
15403	10x12




Package: 25 pcs

CONNECTIONS WITH FERRULES

Conical male


Ref.	Thread	Ø ext. hose
16000	1/8"	6
16001	1/4"	6
16002	1/8"	8
16003	1/4"	8
16004	3/8"	8
16005	1/4"	10
16006	3/8"	10
16007	3/8"	12



Package: 25 pcs

Straight


Ref.	Ø ext. hose
16040	6
16041	8
16042	10
16043	12



Package: 25 pcs

L male


Ref.	Thread	Ø ext. hose
16060	1/8"	6
16061	1/4"	6
16062	1/8"	8
16063	1/4"	8
16064	3/8"	8
16065	1/4"	10
16066	3/8"	10
16067	3/8"	12
16068	1/2"	12



Package: 25 pcs

T central male


Ref.	Thread	Ø ext. hose
16120	1/8"	6
16121	1/4"	6
16122	1/8"	8
16123	1/4"	8
16124	3/8"	8
16125	1/4"	10
16126	3/8"	10
16127	3/8"	12
16128	1/2"	12



Package: 25 pcs

Elbow


Ref.	Ø ext. hose
16100	6
16101	8
16102	10
16103	12



Package: 25 pcs

T EE


Ref.	Ø ext. hose
16160	6
16161	8
16162	10
16163	12



Package: 25 pcs

Blocking nut


Ref.	Ø ext. hose
16300	6
16301	8
16302	10
16303	12



Package: 25 pcs

Brass ferrule

Ref.	Ø ext. hose
16320	6
16321	8
16322	10
16323	12



Package: 100 pcs

AUTOMATIC FITTINGS

Conical male


Ref.	Thread	Ø ext. hose
17000	1/8"	4
17001	1/8"	6
17002	1/4"	6
17003	1/8"	8
17004	1/4"	8
17005	3/8"	8
17006	1/4"	10
17007	3/8"	10
17008	1/4"	12
17009	3/8"	12



Package: 25 pcs

Straight


Ref.	Ø ext. hose
17040	4
17041	6
17042	8
17043	10
17044	12



Package: 25 pcs

L male


Ref.	Thread	Ø ext. hose
17101	1/8"	4
17102	1/8"	6
17104	1/8"	8
17105	1/4"	8
17107	1/4"	10
17108	3/8"	10
17109	1/4"	12
17110	3/8"	12



Package: 25 pcs

L swiveling male


Ref.	Thread	Ø ext. hose
17130	1/8"	4
17131	1/8"	6
17132	1/4"	6
17133	1/8"	8
17134	1/4"	8
17135	3/8"	8
17136	1/4"	10
17137	3/8"	10
17138	1/4"	12
17139	3/8"	12



Package: 25 pcs

Elbow


Ref.	Ø ext. hose
17150	4
17151	6
17152	8
17153	10
17154	12



Package: 25 pcs

Single hollow bolt

Ref.	Thread	Ø ext. hose
17400	M5	4
17401	1/8"	4
17402	1/8"	6
17403	1/4"	6
17404	1/8"	8
17405	1/4"	8
17406	1/4"	10
17407	3/8"	10



Package: 25 pcs

T central male *swiveling

Ref.	Thread	Ø ext. hose
17201	1/8"	4
17202	1/8"	6
17203*	1/4"	6
17204	1/8"	8
17205	1/4"	8
17206*	3/8"	8
17207	1/4"	10
17208	3/8"	10
17209	1/4"	12
17210	3/8"	12



Package: 25 pcs

Female

Ref.	Thread	Ø ext. hose
17020	1/8"	4
17021	1/8"	6
17022	1/4"	6
17023	1/8"	8
17024	1/4"	8
17025	1/4"	10



Package: 25 pcs

T EE

Ref.	Ø ext. hose
17300	4
17301	6
17302	8
17303	10
17304	12



Package: 25 pcs

Bulckhead straight

Ref.	Ø ext. hose
17050	4
17051	6
17052	8
17053	10
17054	12



Package: 25 pcs

MODULAR FILTERS REGULATORS LUBRICATORS

Ideal for use in bodyshops, mechanical garages and wherever there is need to treat the air and adjust the flow. From simple regulators, filters or lubricators to filter groups for pneumatic installation (filter+lubricator) or spray installations (filter+coalescent microfilter).

MICROPRESSURE REGULATOR

Membrane micro regulator, equipped with regulation knob with relieving lock.
Operating air pressure: MAX 16 bar
Regulator range: 0-8 bar
Gauge connection: M 1/8"

Diameter air inlet 1/8"	Ref. 61100
Diameter air inlet 1/4"	Ref. 61101

Package: 1 pcs
Weight: 90 g



Recommended use:



PRESSURE REGULATOR

Membrane micro regulator, equipped with regulation knob with relieving lock.
Operating air pressure: MAX 16 bar
Regulator range: 0-8 bar
Gauge connection: M 1/8"

Diameter air inlet 1/4" - (*)	Ref. 61111
Diameter air inlet 3/8" - (**)	Ref. 61112
Diameter air inlet 1/2" - (***)	Ref. 61113

Package: 1 pcs
(*) Weight: 135 g - (**) Weight: 320 g - (***) Weight: 440 g



Recommended use:



FILTER

Filter with filtering element with 20 micron porosity.
Special reinforced bowl.
Max inlet pressure: MAX 16 bar

Diameter air inlet 1/4" - (*)	Ref. 61121
Diameter air inlet 3/8" - (**)	Ref. 61122
Diameter air inlet 1/2" - (***)	Ref. 61123

Package: 1 pcs
(*) Weight: 115 g - (**) Weight: 230 g - (***) Weight: 355 g



Recommended use:



FILTER REGULATOR

Membrane regulator filter with 20 micron synthetic filtering element, equipped with regulation knob with relieving lock.

Special reinforced cup
Operating air pressure: MAX 16 bar
Regulator range: 0-8 bar
Gauge connection: M 1/8"

Diameter air inlet 1/4" - (*)	Ref. 61131
Diameter air inlet 3/8" - (**)	Ref. 61132
Diameter air inlet 1/2" - (***)	Ref. 61133

Package: 1 pcs - (*) Weight: 115 g - (**) Weight: 230 g - (***) Weight: 355 g



Recommended use:



COALESCENT MICROFILTER

Coalescent microfilter.
Efficiency: 99.9%

Diameter air inlet 1/4" - (*)	Ref. 61201
Diameter air inlet 3/8" - (**)	Ref. 61202
Diameter air inlet 1/2" - (***)	Ref. 61203

Package: 1 pcs
(*) Weight: 115 g - (**) Weight: 225 g - (***) Weight: 345 g



Recommended use:



LUBRICATOR

Lubricator working with oil fogging proportional system.
Special reinforced bowl.
Max inlet pressure: MAX 16 bar

Diameter air inlet 1/4" - (*)	Ref. 61141
Diameter air inlet 3/8" - (**)	Ref. 61142
Diameter air inlet 1/2" - (***)	Ref. 61143

Package: 1 pcs
(*) Weight: 115 g - (**) Weight: 230 g - (***) Weight: 360 g



Recommended use:



FILTER REGULATOR WITH LUBRICATOR

Filter group which associates the features of the filter regulator with those of the lubricator.

Diameter air inlet 1/4" - (*)	Ref. 61151
Diameter air inlet 3/8" - (**)	Ref. 61152
Diameter air inlet 1/2" - (***)	Ref. 61153

Package: 1 pcs
(*) Weight: 310 g - (**) Weight: 675 g - (***) Weight: 975 g



Recommended use:



FILTER - REGULATOR - LUBRICATOR

Filter group which associates the features of the filter, the regulator and those of the lubricator.

Diameter air inlet 1/4" - (*)	Ref. 61161
Diameter air inlet 3/8" - (**)	Ref. 61162
Diameter air inlet 1/2" - (***)	Ref. 61163

Package: 1 pcs
(*) Weight: 380 g - (**) Weight: 850 g - (***) Weight: 1.25 Kg



Recommended use:



ACCESSORIES

Unit connection kit for 1/8" and 1/4"	Ref. 61190
Unit connection kit for 3/8"	Ref. 61191
Unit connection kit for 1/2"	Ref. 61194
Wall unit connection for 1/8" and 1/4"	Ref. 61192
Wall unit connection for 3/8" and 1/2"	Ref. 61193
Gauge with rear connection 1/8", diameter 40 mm (*)	Ref. 61301

Package: 1 pcs - (*) 4 pcs

GAUGE AND AIR COMPRESSED ACCESSORIES

GAUGE

Ref. 61300

Radial connection - M 1/4"
Double pressure gauge range 0 - 12 bar / 0 - 170 psi
Diameter 63 mm

Package: 4 pcs
Weight: 385 g



GAUGE

Double pressure gauge range 0 - 12 bar / 0 - 170 psi

Rear connection - M 1/8" - diameter 40 mm (*) Ref. 61301

Rear connection - M 1/8" - diameter 50 mm (**) Ref. 61302

Rear connection - M 1/4" - diameter 63 mm (***) Ref. 61303

Package: 4 pcs
(*) Weight: 290 g - (**) Weight: 335 g - (***) Weight: 345 g



GAUGE - CEE

Pressure gauge range 0 - 10 bar (only Ref. 61314 double range 0 - 10 bar / 0 - 140 psi)

Rear connection - M 1/4" - diameter 63 mm (*) Ref. 61310

Rear connection - M 1/4" - diameter 80 mm (**) Ref. 61311

Rear connection - M 1/4" - diameter 63 mm (***) Ref. 61314

Package: 4 pcs - (only Ref. 61311 package 1 pcs)
(*) Weight: 405 g - (**) Weight: 230 g - (***) Weight: 405 g



GAUGE

Ref. 61313

Rear connection - M 1/4"
Double pressure gauge range 0 - 10 bar / 0 - 140 psi
Diameter 80 mm

Package: 1 pcs
Weight: 105 g



MICROPRESSURE REDUCER Ref. 61000

Micropressure reducer.
Needle air line tap M 1/4"
Connection: F 1/4"
Pressure gauge range 0 - 12 bar

Package: 3 pcs
Weight: 905 g



PRESSURE REDUCER

Pressure reducer with ceramic filter and gauge.
Outlet with 2 needle air line taps.

Connection - M 3/8" - pressure gauge range 0 - 12 bar (*)	Ref. 61001
Connection - M 1/2" - pressure gauge range 0 - 16 bar (**)	Ref. 61002
Connection - F 1/2" - pressure gauge range 0 - 12 bar (***)	Ref. 61003

Package: 2 pcs - (only Ref. 61003 package 1 pcs)

(*) Weight: 1.3 Kg - (**) Weight: 2.1 Kg - (***) Weight: 1.2 Kg



SAFETY VALVE

Model with connection

Connection - M 1/4" - weight: 340 g - package: 5 pcs	Ref. 61050
Connection - M 3/8" - weight: 520 g - package: 5 pcs	Ref. 61051
Connection - M 3/8" - weight: 520 g - package: 5 pcs	*Ref. 61051/CE
Connection - M 1/2" - weight: 440 g - package: 3 pcs	Ref. 61052
Connection - M 1/2" - weight: 440 g - package: 3 pcs	*Ref. 61052/CE
Connection - M 3/4" - weight: 630 g - package: 2 pcs	Ref. 61053
Connection - M 3/4" - weight: 630 g - package: 2 pcs	*Ref. 61053/CE

(*) Versions at 10 bar with EC approved certificate.



AIR PRESSURE SWITCH

Air pressure switch with drain valve.

Mini monophase model up to 4 HP - (*)	Ref. 61060
Special mini triphase model up to 5.5 HP - (**)	Ref. 61061

Package: 1 pcs

(*) weight: 310 g - (**) weight: 605 g



WITHHOLDING VALVE

Ref. 61065

Horizontal withholding valve with connection for nylon hose
Connection: F 1/2" - M 3/8"

Package: 5 pcs

Weight: 865 g



HOSES

Complete and professional air hose range for any type of use, in various lengths and versions. From high performance Polyurethane to flexible Ragno, to efficient Rilsan to the proven and always reliable Nylon, Rubber and PVC; Walmecc presents the new Rubberflex_{THT/SR} hose with high performance in terms of sturdiness, durability, seal, flexibility and temperature resistance.

STRAIGHT POLYURETHANE

100 m coil

Substrate and cover: 100% polyurethane
Reinforcement: 550/1100 Trevira Hoechst polyester yarn
Operating air pressure: 20 bar - exploding pressure: 60 bar
Temperature: - 25°C + 60°C

Internal diameter 6 mm - external diameter 10 mm	Ref. 60200
Internal diameter 8 mm - external diameter 12 mm	Ref. 60201
Internal diameter 10 mm - external diameter 14.5 mm	Ref. 60202

Package: 1 pcs



STRAIGHT POLYURETHANE

10 m coil with 2 swiveling female 1/4" fittings

Substrate and cover: 100% polyurethane
Reinforcement: 550/1100 Trevira Hoechst polyester yarn
Operating air pressure: 20 bar - exploding pressure: 60 bar
Temperature: - 25°C + 60°C

Internal diameter 6 mm - external diameter 10 mm	Ref. 60210
Internal diameter 8 mm - external diameter 12 mm	Ref. 60211
Internal diameter 10 mm - external diameter 14.5 mm	Ref. 60212

Package: 1 pcs



STRAIGHT POLYURETHANE

25 m coil with 2 swiveling female 1/4" fittings.

Substrate and cover: 100% polyurethane
Reinforcement: 550/1100 Trevira Hoechst polyester yarn
Operating air pressure: 20 bar - exploding pressure: 60 bar
Temperature: - 25°C + 60°C

Internal diameter 6 mm - external diameter 10 mm	Ref. 60220
Internal diameter 8 mm - external diameter 12 mm	Ref. 60221
Internal diameter 10 mm - external diameter 14.5 mm	Ref. 60222

Package: 1 pcs



RAGNO HOSE

50 m coil

Substrate and cover: polyurethane anti-abrasive and thermoplastic rubber
Reinforcement: polyester yarn
Operating air pressure: 20 bar - exploding pressure: 60 bar
Temperature: - 20°C + 60°C

Internal diameter 10 mm - external diameter 15 mm	Ref. 60250
Internal diameter 8 mm - external diameter 12 mm	Ref. 60254

Package: 1 pcs



RAGNO HOSE

Ref. 60252

10 m coil with fittings

Substrate and cover: polyurethane anti-abrasive and thermoplastic rubber

Reinforcement: polyester yarn

Operating air pressure: 20 bar - exploding pressure: 60 bar

Temperature: - 20°C + 60°C

Internal diameter 10 mm - external diameter 15 mm

Package: 1 pcs



SUPERFLEX

High performance and resistance hose, PU (Polyurethane) composite and thermoplastic rubber, reinforced with polyester. Antistatic.

100 m coil

Bottom layer and cover: PU composite and thermoplastic rubber

Reinforcing: polyester fiber

Operating air pressure: 15 - 20 bar

Exploding pressure: 60 bar

Temperature: - 15°C + 70°C

Internal diameter 10 mm - external diameter 15 mm

Ref. 60307

Package: 1 pcs



SUPERFLEX

High performance and resistance hose, PU (Polyurethane) composite and thermoplastic rubber, reinforced with polyester. Antistatic.

12 m coil

Bottom layer and cover: PU composite and thermoplastic rubber

Reinforcing: polyester fiber

Operating air pressure: 15 - 20 bar

Exploding pressure: 60 bar

Temperature: - 15°C + 70°C

Internal diameter 10 mm - external diameter 15 mm

Ref. 60309

Package: 1 pcs



POLYURETHANE SPIRAL HOSE

4 m spiral hose with one straight extension

Operating air pressure: 20 bar - exploding pressure: 60 bar

Temperature: - 25°C + 60°C

Internal diameter 3.6 mm - external diameter 6 mm

Ref. 60030

Internal diameter 5 mm - external diameter 8 mm

Ref. 60031

Package: 5 pcs



POLYURETHANE SPIRAL HOSE

8 m spiral hose with 2 straight extensions

Operating air pressure: 20 bar - exploding pressure: 60 bar

Temperature: - 25°C + 60°C

Internal diameter 3.6 mm - external diameter 6 mm

Ref. 60040

Internal diameter 5 mm - external diameter 8 mm

Ref. 60041

Internal diameter 6.5 mm - external diameter 10 mm

Ref. 60042

Internal diameter 8 mm - external diameter 12 mm

Ref. 60043

Internal diameter 10 mm - external diameter 16 mm *

Ref. 60044

Package: 2 pcs - * Package: 1 pcs



POLYURETHANE SPIRAL HOSE

40 m spiral hose without straight extensions
 Operating air pressure: 20 bar- exploding pressure: 60 bar
 Temperature: - 25°C + 60°C

Internal diameter 5 mm - external diameter 8 mm	Ref. 60051
Internal diameter 6.5 mm - external diameter 10 mm	Ref. 60052
Internal diameter 8 mm - external diameter 12 mm	Ref. 60053
Internal diameter 10 mm - external diameter 16 mm	Ref. 60054

Package: 1 pcs



POLYURETHANE SPIRAL HOSE Ref. 60520

4 m polyurethane spiral hose equipped with PROFI blow gun with silenced nozzle meeting EEC regulations (ref. 50006) and 2 swiveling fittings M 1/4" with protective steel springs.

Package: 5 pcs



RILSAN SPIRAL HOSE

Rilsan spiral hose
 Operating air pressure: 20 bar
 Basic package: 6 x 8 = 270 m; 8 x 10 = 180 m; 10 x 12 = 120 m

Internal diameter 6 mm - ext 8 mm - length 10 m - 27 pcs	Ref. 60007
Internal diameter 6 mm - ext 8 mm - length 15 m - 18 pcs	Ref. 60008
Internal diameter 6 mm - ext 8 mm - length 30 m - 9 pcs	Ref. 60009
Internal diameter 8 mm - ext 10 mm - length 10 m - 18 pcs	Ref. 60012
Internal diameter 8 mm - ext 10 mm - length 15 m - 12 pcs	Ref. 60013
Internal diameter 8 mm - ext 10 mm - length 30 m - 6 pcs	Ref. 60014
Internal diameter 10 mm - ext 12 mm - length 10 m - 12 pcs	Ref. 60017
Internal diameter 10 mm - ext 12 mm - length 15 m - 8 pcs	Ref. 60018
Internal diameter 10 mm - ext 12 mm - length 30 m - 4 pcs	Ref. 60019



STRAIGHT RILSAN HOSE

100 m straight rilsan hose - Operating air pressure: 20 bar

Internal diameter 4 mm - ext 6 mm	Ref. 60326
Internal diameter 6 mm - ext 8 mm	Ref. 60327
Internal diameter 8 mm - ext 10 mm	Ref. 60328
Internal diameter 10 mm - ext 12 mm	Ref. 60329

Package: 1 pcs



RUBBER

100 m straight rubber hose

Operating air pressure: 20 bar

Internal diameter 6 mm - external diameter 14 mm	Ref. 60300
Internal diameter 8 mm - external diameter 17 mm	Ref. 60301

Package: 1 pcs



NYLON

Plastic coated nylon 6 hose

Operating air pressure: 25 bar

Basic package: 6 x 8=270 m; 8 x 10 =180 m; 10 x 12 =120 m

Internal diameter 6 mm - ext 8 mm - length 10 m - 27 pcs	Ref. 60107
Internal diameter 6 mm - ext 8 mm - length 15 m - 18 pcs	Ref. 60108
Internal diameter 6 mm - ext 8 mm - length 30 m - 9 pcs	Ref. 60109
Internal diameter 8 mm - ext 10 mm - length 10 m - 18 pcs	Ref. 60112
Internal diameter 8 mm - ext 10 mm - length 15 m - 12 pcs	Ref. 60113
Internal diameter 8 mm - ext 10 mm - length 30 m - 6 pcs	Ref. 60114
Internal diameter 10 mm - ext 12 mm - length 10 m - 12 pcs	Ref. 60117
Internal diameter 10 mm - ext 12 mm - length 15 m - 8 pcs	Ref. 60118
Internal diameter 10 mm - ext 12 mm - length 30 m - 4 pcs	Ref. 60119



PVC

Ref. 60330

Clear hose in plastified PVC

Operating air pressure: 20 bar

Internal diameter 8 mm - ext 13 mm

Length 100 m

Package: 1 pcs

