

OM-IM-UR PLUS series

Spray guns designed to combine reliability, versatility and price. Their strength has made them the market leaders since their launch in the 50s. But the strength of a product can be seen by the way it devolps, so, in 1999, the HVLP version of the OM was created to meet the needs of the most sensitive markets in terms of product saving and environmental regulations.

The professional IM/OM version originated the creation of the UR PLUS version, with brass components which, considering the quality/price ratio, makes the product also suitable for D.I.Y.

**UR PLUS
UR/S PLUS**
Brass needle and nozzle, improved quality/price ratio without compromising reliability and performance.

UR/S PLUS
Ref. 273

IM - OM
CNC processed single-body brass, for years a guarantee for durability, resilience and performance. In short, IM-OM.

IM
Ref. 262

OM
Ref. 263

OM GREEN
Ref. 290

OM GREEN
Green grip to demonstrate ecology, paint product saving but with Astuomec® IM-OM quality.

OM GREEN (with 680 cc nylon cup) - Ref. 290**

Body: nickel-plated sanded brass
 Air cap: nickel-plated brass
 Needle-nozzle-springs: stainless steel
 Adjustments: product-fan
 Weight: 780 g

Operating air pressure: 2.0 bar
 Air consumption: 200 l/min.
 Ø nozzle: 1.4 - 1.7 - 1.9 - 2.2

HVLP system: low overspray, significant paint product savings

250 cc nylon cup version	(Weight: 670 g)	Ref. 291**
500 cc aluminium cup version	(Weight: 680 g)	Ref. 292**
750 cc aluminium cup version	(Weight: 730 g)	Ref. 293**



NOTE:
add nozzle Ø to Ref. (**)

Recommended use:



IM GREEN Ref. 307**

Camlock suction cup: aluminium 1000 cc
 Body: nickel-plated sanded brass
 Air cap: nickel-plated brass
 Needle-nozzle-springs: stainless steel
 Adjustments: product-fan
 Weight: 1.01 Kg

Operating air pressure: 2.0 bar
 Air consumption: 200 l/min.
 Ø nozzle: 1.4 - 1.7 - 1.9 - 2.2

HVLP system: low overspray, significant paint product savings



NOTE:
add nozzle Ø to Ref. (**)

Recommended use:



IM GREEN Ref. 308**

Bayonet suction cup: aluminium 1000 cc
 Body: nickel-plated sanded brass
 Air cap: nickel-plated brass
 Needle-nozzle-springs: stainless steel
 Adjustments: product-fan
 Weight: 950 g

Operating air pressure: 2.0 bar
 Air consumption: 200 l/min.
 Ø nozzle: 1.4 - 1.7 - 1.9 - 2.2

HVLP system: low overspray, significant paint product savings



NOTE:
add nozzle Ø to Ref. (**)

Recommended use:



IM/SP GREEN Ref. 309**

To be used through pressurized containers, low pressure pumps - Product inlet M1/4"
 Body: nickel-plated sanded brass
 Air cap: nickel-plated brass
 Needle-nozzle-springs: stainless steel
 Adjustments: product-fan
 Weight: 620 g

Operating air pressure: 2.0 bar
 Air consumption: 200 l/min.
 Ø nozzle: 1.4 - 1.7 - 1.9 - 2.2

HVLP system: low overspray significant paint product savings



NOTE:
add nozzle Ø to Ref. (**)

Recommended use:



OM (with 680 cc nylon cup) - Ref. 263**

Body: nickel-plated sanded brass
 Air cap: nickel-plated brass
 Needle-nozzle-springs: stainless steel
 Adjustments: product-fan
 Weight: 780 g

Operating air pressure: 3.0 - 3.5 bar
 Air consumption: 220 l/min.
 Ø nozzle: 1.0 - 1.2 - 1.4 - 1.7 - 1.9 - 2.2 - 2.5 - 3.0 - 3.5 - 4.0

250 cc nylon cup version	(Weight: 670 g)	Ref. 264**
500 cc aluminium cup version	(Weight: 680 g)	Ref. 266**
750 cc aluminium cup version	(Weight: 730 g)	Ref. 265**



NOTE:
 add nozzle Ø to Ref. (**)

Recommended use:



IM Ref. 262**

Camlock suction cup: aluminium 1000 cc
 Body: nickel-plated sanded brass
 Air cap: nickel-plated brass
 Needle-nozzle-springs: stainless steel
 Adjustments: product-fan
 Weight: 1.01 Kg

Operating air pressure: 3.0 - 3.5 bar
 Air consumption: 200 - 350 l/min.
 Ø nozzle: 1.2 - 1.4 - 1.7 - 1.9 - 2.2 - 2.5 - 3.0



NOTE:
 add nozzle Ø to Ref. (**)

Recommended use:



IM Ref. 260**

Bayonet suction cup: aluminium 1000 cc
 Body: nickel-plated sanded brass
 Air cap: nickel-plated brass
 Needle-nozzle-springs: stainless steel
 Adjustments: product-fan
 Weight: 950 g

Operating air pressure: 3.0 - 3.5 bar
 Air consumption: 200 - 350 l/min.
 Ø nozzle: 1.2 - 1.4 - 1.7 - 1.9 - 2.2 - 2.5 - 3.0



NOTE:
 add nozzle Ø to Ref. (**)

Recommended use:



IM/SP Ref. 269**

To be used through pressurized containers, low pressure pumps - Product inlet M1/4"
 Body: nickel-plated sanded brass
 Air cap: nickel-plated brass
 Needle-nozzle-springs: stainless steel
 Adjustments: product-fan
 Weight: 620 g

Operating air pressure: 3.0 - 3.5 bar
 Air consumption: 200 - 350 l/min.
 Ø nozzle: 1.2 - 1.4 - 1.7 - 1.9 - 2.2 - 2.5 - 3.0



NOTE:
 add nozzle Ø to Ref. (**)

Recommended use:

